

A New Strategy of Guidance Command Generation for Re-entry Vehicle

Xie DaoCheng*, Wang ZhongWei, and Zhang WeiHua

National University of Defense Technology, Changsha-410 073, China
*E-mail: xdc_1984@163.com

ABSTRACT

Guidance command for re-entry vehicle can be in various formats, but the Euler angles can be provided directly by gyros, so designers used to develop autopilot with commands of Euler angles. After the generation of commands of angle of attack and sideslip angle, it's important to settle how to convert commands of angle of attack and sideslip angle to commands of Euler angles. Traditional conversion strategy relies on bank angle, but the solution to bank angle comprises complicated calculation and can't be precise. This paper introduces a new conversion strategy of guidance command. This strategy relies on the relative position and velocity measured by seeker, an auxiliary coordinate is established as a transition, the transformation matrix from launch coordinate to body coordinate is solved in a new way, then the commands of Euler angles are obtained. The calculation of bank angle is avoided. The autopilot designed with the converted Euler-angle commands, can track commands of angle of attack and sideslip angle steadily. The vehicle reaches the target point precisely. Simulation results show that the new conversion strategy based on seeker information from commands of angle of attack and sideslip angle to Euler-angle commands is valid.

Keywords: Re-entry vehicle, radar seeker, angle of attack commands, sideslip angle command, Euler angles, transformation matrix

1. INTRODUCTION

Guidance commands for re-entry vehicles are generated based on the line-of-sight (LOS) information. If the guidance command is proper, the vehicle will reach the target point precisely, but the premise is that the autopilot can track guidance command steadily. Usually, the error between guidance command and real state is used to design autopilot. Guidance commands can be in lots of formats, such as acceleration, Euler angles, Euler rate, angle of attack, sideslip angle and so on¹. For re-entry vehicles, Lu² derived body acceleration command, Daigoro³ developed guidance command in the format of angle of attack and sideslip angle.

The advantage of Euler angle command is that the feedback of the controlled variables (Euler-angle body attitude) can be directly provided by inertial measurement unit (IMU) or gyros³. The guidance system will determine the Euler angle commands to be tracked so that the velocity vector is steered according to the guidance law. So designers used to convert angle of attack command and sideslip angle to command of Euler angles³⁻⁵.

After command of angle of attack and sideslip angle are generated, the next problem is how to realize the conversion from commands of angle of attack and sideslip angle to command of Euler angles (yaw, pitch, roll). There exists between velocity coordinate, launch coordinate and body coordinate. Based on the information of heading angle, flight path angle, and bank angle (θ, σ, ν), commands of Euler angles can be derived from transformation matrix. Above method is feasible, but the problem need to be emphasized is: heading

angle, flight path angle, and bank angle are derived based on the navigation data, the navigation data have error after long time flying during booster phase and middle phase, so the value of heading angle, flight path angle, and bank angle have error. If we use above conversion method, commands of Euler angles have error. Furthermore, computation of the bank angle comprises complicated triangular function. In a real flight process, to alleviate the operation burden, bank angle is set to be zero considering that bank angle is always small. Bank angle is treated as zero factitiously, the calculation process is simplified, but error is brought in.

Reentry homing vehicle is equipped with inertial measurement unit and radar seeker, the latter is used for terminal guidance. Dowdle⁶ estimated target maneuver using EKF with the on-board active radar seeker measurements. The measurements were relative range, range rate, line-of-sight (LOS) angles and LOS rates. Balakrishnan^{7,8} has estimated LOS rates from passive measurements of LOS angles alone using modified Polar coordinates. With the method of Carlson filter or Kalman filter⁹⁻¹³, it is possible that relative distance and velocity between vehicle and target can be estimated precisely.

This paper introduces a new strategy of guidance command generation for re-entry vehicle. Transformation matrix from launch coordinate to velocity coordinate is solved relying on the relative position measured by the seeker, instead of the traditional way using heading angle, flight path angle, and bank angle. Through this strategy, commands of angle of attack and sideslip angle are converted into commands of Euler angles, avoiding the calculation process of heading angle, flight path angle, and bank angle.

2. GUIDANCE COMMAND GENERATION OF ANGLE OF ATTACK AND SIDESLIP ANGLE

2.1 Coordinate System Definition

As the downrange of the re-entry phase is short, the earth is modeled as flat. As Fig. 1 shows, $O_E - x_E y_E z_E$ is earth-centred-earth-fixed (ECEF) frame. Define launch coordinate(L): The origin is located at the launch point O_L . The $O_L x_L$ -axis is contained in the horizontal plane at launch point and positive to the launching direction. The $O_L z_L$ -axis is perpendicular to the horizontal plane at launch point and positive to the up. $O_L y_L$ -axis completes a right-handed set. A_0 is launching direction, ϕ_0 is latitude of launch point, λ_0 is longitude of launch point.




Figure 1. Definition of ECEF, launch and body coordinate frames.

Define body coordinate system (B): The origin is located at the vehicle center of mass O_1 and the axes are fixed relative to the vehicle body. The $O_1 x_b$ -axis is along the center line of the vehicle body and positive forward. The $O_1 z_b$ -axis is perpendicular to the $O_1 x_b$ -axis and contained in the longitudinal plane of vehicle. It is positive to the downward. The $O_1 y_b$ -axis is mutually perpendicular to the $O_1 x_b$ and $O_1 z_b$ axes. u, v, w are projections of the velocity in body coordinate, $V_M = \sqrt{u^2 + v^2 + w^2}$. The angle of attack and sideslip angle are written as

$$\begin{aligned} \alpha &= \arcsin(w/u) \\ \beta &= \arctan(v/V_M) \end{aligned} \quad (9)$$

As Fig. 2 shows, O_1 is the vehicle center of mass, O_2 is the projection of O_1 on the local horizontal plane. v is the target position, V_M is the velocity vector.

Target coordinate (T) is local geographic frame (east-north-up) whose origin is located at the target point¹⁴. ϕ_t is latitude of target point, λ_t is longitude of target point.

Define auxiliary coordinate system (A): The origin is located at the vehicle center of mass. The $O_1 z_f$ -axis is parallel to the $O_1 z_T$ -axis and positive up. $O_1 x_A$ -axis is parallel to $x_T O_T y_T$ plane and positive to the target. $O_1 y_f$ -axis completes a right-handed set.

Define velocity coordinate system (V): The origin is located




Figure 2. Definition of target, velocity, auxiliary and control coordinate frames.

at the vehicle center of gravity. The $O_1 x_v$ -axis is aligned with the vehicle velocity vector. The $O_1 z_v$ -axis is perpendicular to the $O_1 x_v$ -axis and contained in the longitudinal symmetry plane of vehicle. It is positive to the up. The $O_1 y_v$ -axis completes a right-handed set.

Define control coordinate system (C): The origin is located at the target point. The $O_T x_c$ -axis is aligned with the target to vehicle range vector. The $O_T y_c$ -axis is perpendicular to the $O_T x_c$ -axis and contained in the horizontal plane. It is positive to the right. The $O_T z_c$ -axis completes a right-handed set.

Components of re-entry position in target coordinate system are x_T, y_T, z_T ; components of re-entry velocity are V_{xT}, V_{yT}, V_{zT} . Relative position and velocity vectors are determined by combining navigation with radar seeker. The included angle between $O_2 O_T$ and λ_e is elevation angle λ_e and the included angle between $O_2 O_T$ and λ_a is azimuth angle λ_a .

$$\lambda_e = \arcsin \left[z_T / \sqrt{x_T^2 + y_T^2 + z_T^2} \right] \quad (1)$$

$$\lambda_a = \arctan [y_T / x_T]$$

See Fig. 1, $O_2 O_T$ is the projection of $O_1 O_T$ on the horizontal plane $x_T O_T y_T$. Note the definition of control coordinate (C) and auxiliary coordinate (A), $O_1 y_f$ and $O_T y_s$ both are vertical to $O_1 O_2 O_T$ plane. The transformation matrix from auxiliary coordinate to control coordinate is $C_F^S = R_y(-\lambda_e)$. R_y indicates rotation about y-axis for the specified angle.

$V_{x_C}, V_{y_C}, V_{z_C}$ are projections of the velocity vector in control coordinate; it is expressed as in Eqn (2) where the transformation matrix C_T^F from target coordinate to auxiliary coordinate is expressed in later section 3 in detail.

$$\begin{bmatrix} V_{x_C} \\ V_{y_C} \\ V_{z_C} \end{bmatrix} = C_F^S C_T^F \begin{bmatrix} V_{x_T} \\ V_{y_T} \\ V_{z_T} \end{bmatrix} \quad (2)$$

γ_D is the angle between the velocity vector and local horizontal plane, γ_T is the angle between velocity vector and local vertical plane (usually called diving plane in re-entry guidance).




Figure 3. Definition of γ_D and $\gamma_T = -\arctan \left[\frac{V_{zs}}{\sqrt{V_{xs}^2 + V_{ys}^2}} \right]$.

Note that $O_1O_2y_C$ plane is vertical to $O_1O_2y_C$ plane is horizontal. So we can write γ_D and γ_T as follows:

$$\begin{aligned} \gamma_D &= \text{atan}(V_{zC}/V_{xC}) + \lambda_e \\ \gamma_T &= \text{atan} \left[\frac{V_{yC}}{\sqrt{V_{xC}^2 + V_{zC}^2}} \right] \end{aligned} \quad (3)$$

2.2 Commands of Angle of attack and Sideslip Angle

Optimal guidance law based on LQR theory is given by^{15,16}

$$\begin{cases} \dot{\gamma}_D = -4\dot{\lambda}_e - 2(\lambda_e + \gamma_{DF})/T_g \\ \dot{\gamma}_T = 3\dot{\lambda}_a \cos \lambda_e \end{cases} \quad (4)$$

where T_g is time-to-go, γ_{DF} represents the terminal value of γ_D specified a priori by guidance system requirement, which means that the designers desire the vehicle to impact the target in a particular direction in diving plane.

We obtain the corresponding commanded body accelerations (not including gravity) in the y_v and z_v axes as²

$$\begin{aligned} \dot{W}_{yv} &= -v\dot{\gamma}_T - g_{yv} \\ \dot{W}_{zv} &= v \cos \gamma_T \dot{\gamma}_D - g_{zv} \end{aligned} \quad (5)$$

where V_M is the velocity; g_{yv}, g_{zv} are components of gravity in the y_v and z_v axes. Eqn (5) indicate that for γ_D and γ_T to change as specified by the guidance law, the apparent acceleration components \dot{W}_{yv} and \dot{W}_{zv} should be applied on the y and z direction of the velocity coordinate frame.

The corresponding guidance commands of angle of attack α_c and sideslip angle β_c are

$$\begin{aligned} \alpha_c &= -\frac{\alpha_{TOT} \dot{W}_{yv}}{\sqrt{\dot{W}_y^2 + \dot{W}_z^2}} \\ \beta_c &= -\frac{\alpha_{TOT} \dot{W}_{zv}}{\sqrt{\dot{W}_y^2 + \dot{W}_z^2}} \end{aligned} \quad (6)$$

where \dot{W}_y and \dot{W}_z are projections of current apparent acceleration in velocity coordinates, α_{TOT} is total angle of attack, $\alpha_{TOT} = \sqrt{\alpha^2 + \beta^2}$.

3. TRADITIONAL SOLUTION TO COMMANDS OF EULER ANGLES

The transformation matrix between launch coordinate (L), velocity coordinate (V) and body coordinate (B) can be expressed as

$$C_L^B(\phi_c, \psi_c, \gamma_c) = C_V^B(\alpha_c, \beta_c) C_L^V \quad (7)$$

Note Eqn (7), after the derivation of α_c and β_c , the key step in the solution to commands of Euler-angle body attitude ψ_c, θ_c, ϕ_c (yaw command, pitch command, roll command) is the transformation matrix from launch coordinate to velocity coordinate C_L^V . The traditional solution strategy is

$$C_L^V = R_x(v) R_z(\sigma) R_y(\theta) \quad (8)$$

C_L^V is achieved through rotation by heading angle ξ , flight path angle γ , and bank angle μ in the sequence Z-Y-X(3-2-1).

Based on the velocity projection in launch coordinate v_{Lx}, v_{Ly}, v_{Lz} and the norm of velocity vector V_M , heading angle ξ and, flight path γ are expressed as

$$\begin{aligned} \xi &= \arcsin(-v_{Ly}/V_M) \\ \gamma &= \arctan(v_{Lz}/v_{Lx}) \end{aligned} \quad (9)$$

Based on the current attitude ϕ, ψ, γ (yaw, pitch, roll) and θ, σ , bank angle v is expressed as follows¹⁷.

$$\begin{aligned} \sin \beta &= \cos \theta [\cos \gamma \sin(\psi - \sigma) + \sin \phi \sin \gamma \cos(\psi - \sigma)] - \sin \theta \cos \phi \sin \gamma \\ \sin \alpha &= \{\cos \theta [\sin \phi \cos \gamma \cos(\psi - \sigma) - \sin \gamma \sin(\psi - \sigma)] - \sin \theta \cos \phi \cos \gamma\} / \cos \beta \\ \sin \mu &= (\cos \alpha \sin \beta \sin \phi - \sin \alpha \sin \beta \cos \gamma \cos \psi) + \cos \beta \sin \gamma \cos \phi / \cos \theta \end{aligned} \quad (10)$$

Note that solution to v is complicated, firstly we should get the value of angle of attack α and sideslip angle β .

See Eqn (7), the dimension of transformation matrix is 3×3 , three Eqns can be obtained, then ϕ_c, ψ_c, γ_c are solved. The solution Eqn is described in reference¹.

4. A NEW SOLUTION STRATEGY TO COMMANDS OF EULER ANGLES

Without the information of θ, σ, v , the transformation matrix C_L^V from launch coordinate to velocity coordinate can't be described directly. Introduction of auxiliary coordinate (A) is just to realize this transformation.

Based on the defined auxiliary coordinate (A) and target coordinate (T), the transformation matrix C_L^V is expressed in this paper as

$$C_L^V = C_F^V C_T^F C_L^T \quad (11)$$

From Eqn (10), we note that auxiliary coordinate (A) is transition between target coordinate (T) and velocity coordinate (V).

4.1 Transformation Matrixes

The transformation matrix C_L^T from launch coordinate to target coordinate is

$$C_L^T = R_y(-\phi_t) R_x(\lambda_t - \lambda_0) R_y(\phi_0) R_z(A_0) \quad (12)$$

Based on the definition of γ_D and γ_T , transformation matrix C_F^V from auxiliary coordinate to velocity coordinate is as follows

$$C_F^V = R_z(\gamma_T)R_y(\gamma_D) = \begin{bmatrix} \cos \gamma_T \cos \gamma_D & \sin \gamma_T & -\cos \gamma_T \sin \gamma_D \\ -\sin \gamma_T \cos \gamma_D & \cos \gamma_T & \sin \gamma_T \sin \gamma_D \\ \sin \gamma_D & 0 & \cos \gamma_D \end{bmatrix} \quad (13)$$

Rotate velocity coordinate by angle β_c and α_c in the sequence Z-Y(3-2), body coordinate is obtained. So the transformation matrix C_V^B from velocity coordinate to body coordinate is

$$C_V^B = R_y(\alpha_c)R_z(\beta_c) = \begin{bmatrix} \cos \alpha_c \cos \beta_c & \cos \alpha_c \sin \beta_c & -\sin \alpha_c \\ -\sin \beta_c & \cos \beta_c & 0 \\ \sin \alpha_c \cos \beta_c & \sin \alpha_c \sin \beta_c & \cos \alpha_c \end{bmatrix} \quad (14)$$

4.2 Euler-angle Commands Conversion-based on Relative Position Information

After the solution of C_L^T and C_F^V , to get C_L^V , the transformation matrix C_T^F from target coordinate to auxiliary coordinate is significant, which have been mentioned frontally in Section 2.1.

See Fig 4, and also note the definition of auxiliary coordinate(A) and target coordinate(T), O_1z_f is parallel to O_Tz_T axis, O_1x_A is parallel to $x_TO_1z_T$ plane, so $x_fO_1y_f$ plane is parallel to $x_TO_Ty_T$ plane.

O_2O_T is the projection of line-of sight O_1O_T on horizontal plane $x_TO_Tz_T$, and O_1x_A is toward the target, so O_1x_A is parallel to O_2O_T . By translation of O_1x_A axis to target point O_T , note that $O_Tx'_f$ locates at the extension of O_2O_T , and $O_Tx'_f$ also locates in the horizontal plane $x_TO_Ty_T$. θ_r is defined as the included angle between O_2O_T and O_Ty_T , then the included angle between $O_Tx'_f$ and O_Ty_T is $\pi/2-\theta_r$.

Rotate about O_Tz_T axis by an angle $(\pi/2-\theta_r)$ clockwise, the transformation matrix C_T^F from target coordinate to auxiliary coordinate is obtained.

$$\begin{aligned} C_T^F &= R_z(-3\pi/2 - \theta_r) \\ &= \begin{bmatrix} \cos(\theta_r - 3\pi/2) & \sin(\theta_r - 3\pi/2) & 0 \\ -\sin(\theta_r - 3\pi/2) & \cos(\theta_r - 3\pi/2) & 0 \\ 0 & 0 & 1 \end{bmatrix} \\ &= \begin{bmatrix} -\sin \theta_r & \cos \theta_r & 0 \\ -\cos \theta_r & -\sin \theta_r & 0 \\ 0 & 0 & 1 \end{bmatrix} \\ &= \begin{bmatrix} -x_T/\sqrt{x_T^2 + y_T^2} & y_T/\sqrt{x_T^2 + y_T^2} & 0 \\ -y_T/\sqrt{x_T^2 + y_T^2} & -x_T/\sqrt{x_T^2 + y_T^2} & 0 \\ 0 & 0 & 1 \end{bmatrix} \end{aligned} \quad (15)$$

In Eqn (15), x_T and y_T are re-entry position projections in target coordinate, it's measured by complex navigation with radar seeker and IMU data.

Substituting Eqns (12),(13), and (15) into Eqn (11), we have

$$\begin{aligned} C_L^V &= C_F^V C_T^F C_g^T \\ &= R_z(\gamma_T)R_y(\gamma_D)R_z(\theta_r - 3\pi/2)R_y(-\phi)R_x(\lambda_r - \lambda_0)R_y(\phi)R_z(A_0) \end{aligned}$$




Figure 4. Transformation from target coordinate(T) to auxiliary coordinate(A).

(16)

Substituting Eqns (16) and (14) into Eqn (7), the transformation matrix C_L^B from launch coordinate to body coordinate can be written as

$$C_L^B = C_V^B C_L^V = [d_{ij(i=j=3)}] \quad (17)$$

Commands of Euler angles (ϕ_c, ψ_c, γ_c) are attitudes that we desire the vehicle to achieve. The transformation C_L^B is achieved through rotation by Euler-angle commands ϕ_c, ψ_c, γ_c in the sequence Z-Y-X(3-2-1).

$$\begin{aligned} C_L^B &= R_x(\gamma_c)R_z(\psi_c)R_y(\phi_c) \\ &= \begin{bmatrix} \cos \phi_c \cos \psi_c & \sin \psi_c \\ -\cos \phi_c \sin \psi_c \cos \gamma_c + \sin \phi_c \sin \gamma_c & \cos \psi_c \cos \gamma_c \\ -\cos \phi_c \sin \psi_c \sin \gamma_c + \sin \phi_c \cos \gamma_c & -\cos \psi_c \sin \gamma_c \\ -\sin \phi_c \cos \psi_c \\ \sin \phi_c \sin \psi_c \cos \gamma_c + \cos \phi_c \sin \gamma_c \\ -\sin \phi_c \sin \psi_c \sin \gamma_c + \cos \phi_c \cos \gamma_c \end{bmatrix} \end{aligned} \quad (18)$$

Compare Eqn (18) with Eqn (17), the commands of Euler-angle body attitude in launch coordinate are expressed as

$$\phi_c = \begin{cases} \arctan(-d_{13}/d_{11}) & d_{11} > 0 \\ \pi \cdot \text{sgn}(-d_{13}) + \arctan(-d_{13}/d_{11}) & d_{11} < 0 \\ \pi \cdot \text{sgn}(-d_{13})/2 & d_{11} = 0 \end{cases} \quad (19)$$

$$\psi_c = -\arcsin(d_{12})$$

$$\gamma_c = \arctan(-d_{32}/d_{22})$$

5. RESULTS AND DISCUSSION

The latitudes and longitudes of launch point and target point are presumed. The seeker starts work when the relative distance between vehicle and target is short than 150 km. In the re-entry phase, the vehicle has no thrust, the body attitude is changed by the control moment produced by the actuator.

The initial flight parameters are listed in Table 1. Simulation is realized with Matlab/Simulink software, and the simulation finishes when the flight height of the vehicle is

Table 1. Initial flight parameters of re-entry vehicle (in launch coordinate)

Reentry parameters	Values
Position (m)	1588616.63186, -135167.42081, 104991.51512
Velocity (m/s)	2369.47627, -2836.55286, -55.18684
Angular rates (rad/s)	-0.0053890820, 0.00484471501, -0.00268215946
Euler angles (rad)	-0.9315217715, 0.07032788799, -0.02611680311

below zero.

Noise of IMU and radar seeker are considered in simulation, the measurement noise of radar seeker is shown in Table 2. Estimation error of relative position is quite small

Table 2. Seeker measurement noise (one σ)

Seeker		
Relative range	LOS angle along azimuth and elevation	LOS rate along azimuth and elevation
0.8m	0.2°	0.2°/s

using complex navigation⁹⁻¹³.

5.1 Convert α_c, β_c to $\varphi_c, \psi_c, \gamma_c$

Guidance commands of angle of attack and sideslip angle are generated in earlier section. The maximum available angle of attack is 25 degree, and actuator deflection is limited to $\pm 30^\circ$.

In re-entry phase, the guidance and control system start work when the dynamic pressure is above a preset-value.

The commands of Euler angles using the new conversion strategy are shown in Fig. 5.

5.2 Tracking Performance of α_c and β_c

Next we will apply this new guidance command conversion strategy to the re-entry guidance and control system design, which mainly comprises three parts; commands of angle of attack α_c and sideslip angle β_c ; command conversion from α_c, β_c to $\varphi_c, \psi_c, \gamma_c$; develop autopilot with Euler-angle commands $\varphi_c, \psi_c, \gamma_c$.

Note that commands of angle of attack and sideslip angle are proper, such guidance command will guidance the vehicle to target point. Figure 6 shows the tracking performance of Euler-angle command ψ_c, θ_c, ϕ_c , Figure 7 shows the response to Euler-angle command $\varphi_c, \psi_c, \gamma_c$ (0.5°). The autopilot developed with commands of Euler angles ψ_c, θ_c, ϕ_c can track the commands of Euler angles steadily.

Whether the vehicle can track guidance commands of angle of attack α_c and sideslip angle β_c , the focus is that the new conversion strategy from α_c, β_c to $\varphi_c, \psi_c, \gamma_c$ is right. To evaluate the correctness of this new conversion strategy, the tracking performance of commands of angle of attack and sideslip angle should be analyzed.

The tracking performance of command of angle of attack is shown in Fig. 8, α_c is command of angle of attack, α is the




Figure 5. Commands of Euler angles. (a) command of pitch angle; (b) command of yaw angle; (c) command of roll angle.







Figure 6. Tracking performance with commands of Euler angles. (a) pitch command (b) yaw command and (c) roll command.



(a)



(b)




(c)

Figure 7. Response to commands of Euler angles: (a) in pitch, (b) in yaw, and (c) in roll.


actual angle of attack of re-entry vehicle.

The tracking performance of command of sideslip angle is shown in Fig. 9, β_c is command of sideslip angle, β is the actual sideslip angle of re-entry vehicle.

The re-entry vehicle tracks the guidance commands of angle of attack and sideslip angle steadily, the tracking error is within $\pm 15^\circ$. Considering that there is a time lag between real body attitude and guidance commands, so the real tracking error is far smaller than $\pm 15^\circ$, which can be shown assuredly in Figs. 8(a) and 9(a).




(a)




(b)

Figure 8. Tracking performance with command angle of attack; (a) curves of α and α_c , (b) tracking error with α_c .



(a)



(b)

Figure 9. Tracking performance with command of sideslip angle; (a) curves of β and β_c , (b) tracking error with β_c .

Euler-angle commands Ψ_c, θ_c, ϕ_c are obtained with the new strategy, and autopilot developed with Ψ_c, θ_c, ϕ_c can track α_c, β_c steadily. So the conversion strategy from α_c, β_c to ϕ_c, Ψ_c, γ_c is right. The precise tracking assures precise implement of guidance command, then the vehicle will reach the target point steered by the guidance law precisely.

The re-entry position in target coordinate (x_T, y_T, z_T) is shown in Fig. 10, and the impact point error is $(-5.168, 0.58, 3.839)$ m. Radar seeker and IMU noises are considered in simulation, so there must be small deviation of x_T, y_T, z_T from the true value. The errors in x_T, z_T will influence the conversion process, so Euler angle command is a little different from the idealistic value, then re-entry trajectory is slightly separated from idealistic trajectory. The reentry velocity, curves of γ_D and γ_T are shown in Figs. 11-13.

Small impact point error also indicates that the new




Figure 10. Position of reentry vehicle in target coordinate system.




Figure 11. Reentry velocity varying with time.




Figure 12. Curve of γ_D varying with time.




Figure 13. Curve of γ_T varying with time.

guidance command conversion strategy is right.

6 CONCLUSIONS

For re-entry vehicle, a new conversion strategy from commands of angle of attack and sideslip angle to commands of Euler angles is brought in. This strategy relies on the relative position and velocity measured by seeker, an auxiliary coordinate is established as a transition, transformation matrix C_L^V from launch coordinate to velocity coordinate is solved in a novel way.

After commands of angle of attack α_c and sideslip angle β_c are generated, commands of Euler angles Ψ_c, θ_c, ϕ_c can be obtained with this new conversion strategy.

The main calculation in this strategy is matrix multiplication, and this strategy doesn't rely on the information of θ, σ, v , so the complicated calculation of θ, σ, v are avoided.

The correctness of the new conversion strategy from α_c, β_c to ϕ_c, Ψ_c, γ_c can be testified from two aspects.

1. On the premise that α_c, β_c are right and the autopilot can track commands of Euler angles ϕ_c, Ψ_c, γ_c steadily, the re-entry vehicle can track commands of angle of attack

- α_c and sideslip angle β_c steadily and precisely.
- The vehicle reaches the target point precisely, which indicates that the guidance command is implemented fully, and the vehicle approaches the target steered by the guidance law.

REFERENCES

- George, M. S. Missile guidance and control systems. New York: Springer-Verlag, 2003, pp. 61-62.
- Ping, Lu.; David, B.D. & John, D.S. Adaptive terminal guidance for hypervelocity impact in specified direction. *J. Guidance, Control Dyn.*, 2006, **29**(2), 269-78.
- Daigoro, I.; Jennifer, G. & John, V. Re-entry vehicle flight controls design guidelines: Dynamic inversion. NASA Report, NASA/TP-2002-210771, 2002. pp.16-20.
- James, R.C. & Donald, T.S. Dynamic conversion of flight path commands to body attitude commands. *In Proceedings of the American Control Conference*. Anchorage: IEEE, 2002.
- Kevin, P.B.; Michael, W.O. & David, D.D. Optimal guidance command generation and tracking for reusable launch vehicle reentry. AIAA Guidance, Navigation, and Control Conference and Exhibit. August 2006. 1-23.
- Dowdle, J.R.; Athans, M. & Gully, S. An optimal control and estimation algorithm for missile endgame guidance. *In Proceedings of IEEE Conference on Decision and Control*. 1982.
- Balakrishnan, S.N. & Speuer, J.L. Coordinate transformation based filter for improved target tracking. *J. Guidance, Control Dyn.*, 1986, **9**(6), 704-609.
- Balakrishnan, S. N. Extension to modified polar coordinates and applications with passive measurements. *J. Guidance, Control Dyn.*, 1989, **12**(6), 906-912.
- Dwivedi, P.N.; Tiwari, S.N. & Bhattacharya, A. A ZEM based effective integrated estimation and guidance of interceptors. AIAA Guidance, Navigation and Control Conference, 2011, AIAA 2011-6420.
- Ananthasayanam, M.R.; Sarkar, A.K.; Bhattacharya, A. Tiwari, P.K. & Vohra, P. Nonlinear observer state estimation from seeker measurements and seeker-radar measurements fusion. AIAA Guidance, Navigation and Control Conference and Exhibit, 2005, 1-25.
- Dwivedi, P.N.; Tiwari, S.N.; Bhattacharya, A. & Padhi, R. A ZEM based effective integrated estimation and guidance of interceptors in terminal phase. AIAA Guidance, Navigation and Control Conference, 2010, 1-25.
- Srinivasan, T.; Kar, P.K.; Sarkar, A.K. & Ananthasayanam, M.R. Performance study of radar and seeker estimator in a realistic tactical scenario. AIAA Guidance, Navigation and Control Conference and Exhibit, 2008, 1-21.
- Sarkar, A.K.; Ananthasayanam, M.R.; Srinivasan, T. & Kar, P.K. Comparison of the radar and seeker modes of pursuer guidance. *J. Guidance, Control Dyn.*, 2009, **32**(6), 1912-1920.
- Gorecki, R.M. A baseline 6 degree of freedom (DOF) mathematical model of a generic missile. DSTO Systems Sciences Laboratory Report, DSTO-TR-0931, 2003, pp.2-7.
- Lian, B.H.; Hyochoong, B. & John, E.H. Adaptive backstepping control based autopilot design for re-entry vehicle. AIAA Guidance, Navigation, and Control Conference and Exhibit, 2004, 1-10.
- Yang, J.C.; Hu, J. & Ni, M.L. Adaptive guidance law design based on characteristic model for re-entry vehicles. *Sci. China Inf. Sci.*, 2008, **51**(12), 2005-2021.

Contributors



Mr Daocheng Xie obtained his MS from National University of Defense Technology, Changsha, China, in 2008. He is currently pursuing PhD from NUDT. His research interests are: Guidance and attitude control of aircrafts, hardware-in-the-loop simulation for flight control.



Dr Zhongwei Wang obtained his PhD from National University of Defense Technology in 1995. Presently, working as a Professor at College of Aerospace Science and Engineering, National University of Defense Technology. His research areas are: Navigation, guidance and attitude control of aircrafts and spacecrafts.



design.

Dr Weihua Zhang obtained his PhD from National University of Defense Technology in 1999. Presently, working as a Dean and Professor of College of Aerospace Science and Engineering, National University of Defense Technology. His research areas are: Advanced attitude control method, multi-disciplinary optimization on aircraft